

SKY

- Door- or wall-mount air conditioners
- Condizionatori per montaggio a porta o parete
- Klimageräte zur Installation an der Tür oder der Wand
- Climatiseurs pour montage sur porte ou mural
- Acondicionadores para montaje en puerta o pared



Item Codice Artikelnummer Code Referencia	Cooling capacity Potenza frigorifera Kühlleistung Puissance frigorifique Potencia frigorífica EN14511 - A35A35	Power supply Alimentazione Stromversorgung Alimentation Alimentación	Dimensions Dimensioni Abmessungen Dimensions Medidas WxHxD	Conformity Conformità Konformität Conformité Conformidad
SKY10BT0B	1050 W	230 V 1~ 50-60 Hz	400 x 950 x 233 mm	CE
SKY10CT0B	1050 W	115 V 1~ 50-60 Hz	400 x 950 x 233 mm	CE
SKY10GT0B	1050 W	400/440 V 2~ 50-60 Hz	400 x 950 x 233 mm	CE
SKY15BT0B	1550 W	230 V 1~ 50-60 Hz	400 x 950 x 233 mm	CE
SKY15CT0B	1550 W	115 V 1~ 50-60 Hz	400 x 950 x 233 mm	CE
SKY15GT0B	1550 W	400/440 V 2~ 50-60 Hz	400 x 950 x 233 mm	CE
SKY20BT0B	2050 W	230 V 1~ 50-60 Hz	400 x 1265 x 236 mm	CE
SKY20CT0B	2050 W	115 V 1~ 50-60 Hz	400 x 1265 x 236 mm	CE
SKY20LT0B	2050 W	400 V 3~ 50-60 Hz	400 x 1265 x 236 mm	CE

FLY

- Door- or wall-mount air conditioners
- Condizionatori per montaggio a porta o parete
- Klimageräte zur Installation an der Tür oder der Wand
- Climatiseurs pour montage sur porte ou mural
- Acondicionadores para montaje en puerta o pared



Item Codice Artikelnummer Code Referencia	Cooling capacity Potenza frigorifera Kühlleistung Puissance frigorifique Potencia frigorífica EN14511 - A35A35	Power supply Alimentazione Stromversorgung Alimentation Alimentación	Dimensions Dimensioni Abmessungen Dimensions Medidas WxHxD	Conformity Conformità Konformität Conformité Conformidad
FLY11BTUB	1100 W	230 V 1~ 50-60 Hz	495 x 1697 x 195 mm	CE - UL
FLY11KTUB	1100 W	400/460 V 2~ 50-60 Hz	495 x 1697 x 195 mm	CE - UL
FLY15BTUB	1500 W	230 V 1~ 50-60 Hz	495 x 1697 x 195 mm	CE - UL
FLY15KTUB	1500 W	400/460 V 2~ 50-60 Hz	495 x 1697 x 195 mm	CE - UL
FLY20BTUB	2000 W	230 V 1~ 50-60 Hz	495 x 1697 x 195 mm	CE - UL
FLY20HTUB	2000 W	400 V 3~ 50 Hz/460 V 3~ 60 Hz	495 x 1697 x 195 mm	CE - UL
FLY25BTUB	2500 W	230 V 1~ 50-60 Hz	495 x 1697 x 235 mm	CE - UL
FLY25HTUB	2500 W	400 V 3~ 50 Hz/460 V 3~ 60 Hz	495 x 1697 x 235 mm	CE - UL
FLY32BTUB	3200 W	230 V 1~ 50-60 Hz	495 x 1697 x 235 mm	CE - UL
FLY32HTUB	3200 W	400 V 3~ 50 Hz/460 V 3~ 60 Hz	495 x 1697 x 235 mm	CE - UL

EGO

- Door- or wall-mount air conditioners
- Condizionatori per montaggio a porta o parete
- Klimageräte zur Installation an der Tür oder der Wand
- Climatiseurs pour montage sur porte ou mural
- Acondicionadores para montaje en puerta o pared



Item Codice Artikelnummer Code Referencia	Cooling capacity Potenza frigorifera Kühlleistung Puissance frigorifique Potencia frigorífica EN14511 - A35A35	Power supply Alimentazione Stromversorgung Alimentation Alimentación	Dimensions Dimensioni Abmessungen Dimensions Medidas WxHxD	Conformity Conformità Konformität Conformité Conformidad
EGOS3BT1B	300 W	230 V 1~ 50-60 Hz	525 x 345 x 136 mm	CE
EGO04BT1B	380 W	230 V 1~ 50-60 Hz	285 x 460 x 180 mm	CE
EGO04BTVBX0000	380 W	230 V 1~ 50-60 Hz	285 x 460 x 180 mm	CE - UL
EGO04CT1B	380 W	115 V 1~ 50-60 Hz	285 x 460 x 180+35 mm	CE
EGO06BT1B	640 W	230 V 1~ 50-60 Hz	316 x 606 x 212 mm	CE
EGO06BTVBX0000	640 W	230 V 1~ 50-60 Hz	316 x 606 x 212 mm	CE - UL
EGO06CT1B	640 W	115 V 1~ 50-60 Hz	316 x 606 x 212+42 mm	CE
EGO06GT1B	640 W	400/440 V 2~ 50-60 Hz	316 x 606 x 212+58 mm	CE
EGO08BT1B	820 W	230 V 1~ 50-60 Hz	348 x 783 x 216 mm	CE
EGO08BTVBX0000	820 W	230 V 1~ 50-60 Hz	348 x 783 x 216 mm	CE - UL
EGO08CT1B	820 W	115 V 1~ 50-60 Hz	348 x 783 x 216+42 mm	CE
EGO08GT1B	820 W	400/440 V 2~ 50-60 Hz	348 x 783 x 216+58 mm	CE
EGO10BT1B	1000 W	230 V 1~ 50-60 Hz	348 x 783 x 216 mm	CE
EGO10BTVBX0000	1000 W	230 V 1~ 50-60 Hz	348 x 783 x 216 mm	CE - UL
EGO10CT1B	1000 W	115 V 1~ 50-60 Hz	348 x 783 x 216+42 mm	CE
EGO10GT1B	1000 W	400/440 V 2~ 50-60 Hz	348 x 783 x 216+58 mm	CE
EGO10KTVBX0000	1000 W	400/460 V 2~ 50-60 Hz	348 x 783 x 216+58 mm	CE - UL
EGO12BT1B	1250 W	230 V 1~ 50-60 Hz	405 x 999 x 237 mm	CE
EGO12BTVBX0000	1250 W	230 V 1~ 50-60 Hz	405 x 999 x 237 mm	CE - UL
EGO12CT1B	1250 W	115 V 1~ 50-60 Hz	405 x 999 x 237 mm	CE
EGO12GT1B	1250 W	400/440 V 2~ 50-60 Hz	405 x 999 x 237 mm	CE
EGO16BT1B	1600 W	230 V 1~ 50-60 Hz	405 x 999 x 237 mm	CE
EGO16BTVBX0000	1600 W	230 V 1~ 50-60 Hz	405 x 999 x 237 mm	CE - UL
EGO16CT1B	1600 W	115 V 1~ 50-60 Hz	405 x 999 x 237 mm	CE
EGO16GT1B	1600 W	400/440 V 2~ 50-60 Hz	405 x 999 x 237 mm	CE
EGO16KTVBX0000	1600 W	400/460 V 2~ 50-60 Hz	405 x 999 x 237 mm	CE - UL
EGO20BT1B	2000 W	230 V 1~ 50-60 Hz	405 x 999 x 237 mm	CE
EGO20BTVBX0000	2000 W	230 V 1~ 50-60 Hz	405 x 999 x 237 mm	CE - UL
EGO20CT1B	2000 W	115 V 1~ 50-60 Hz	405 x 999 x 237 mm	CE
EGO20LT1B	2000 W	400 V 3~ 50-60 Hz	405 x 999 x 237 mm	CE
EGO20NTVBX0000	2000 W	460 V 3~ 60 Hz	405 x 999 x 237 mm	CE - UL
EGO30BT1B	2900 W	230 V 1~ 50-60 Hz	500 x 1270 x 336 mm	CE
EGO30LT1B	2900 W	400 V 3~ 50-60 Hz	500 x 1270 x 336 mm	CE
EGO30NTVBX0000	2900 W	460 V 3~ 60 Hz	500 x 1270 x 336 mm	CE - UL
EGO40BT1B	3850 W	230 V 1~ 50-60 Hz	500 x 1270 x 336 mm	CE
EGO40LT1B	3850 W	400 V 3~ 50-60 Hz	500 x 1270 x 336 mm	CE
EGO40NTVBX0000	3850 W	460 V 3~ 60 Hz	500 x 1270 x 336 mm	CE - UL
EGO60MTEB	5800 W	400 V 3~ 50 Hz	600 x 2000 x 387 mm	CE
EGO60NTEB	6050 W	460 V 3~ 60 Hz	600 x 2000 x 387 mm	CE
EGO80MTEB	7600 W	400 V 3~ 50 Hz	800 x 2000 x 387 mm	CE
EGO80NTEB	7950 W	460 V 3~ 60 Hz	800 x 2000 x 387 mm	CE
EGO A0MTEB	9400 W	400 V 3~ 50 Hz	800 x 2000 x 387 mm	CE
EGO A0NTEB	9850 W	460 V 3~ 60 Hz	800 x 2000 x 387 mm	CE
EGO A5MTEB	14800 W	400 V 3~ 50 Hz	800 x 2000 x 550 mm	CE
EGO A5NTEB	15150 W	460 V 3~ 60 Hz	800 x 2000 x 550 mm	CE

DEK

- Roof-mount air conditioners
- Condizionatori per montaggio a tetto
- Klimageräte zur Installation auf dem Dach
- Climatiseurs pour montage sur toit
- Acondicionadores para montaje en techo



Item Codice Artikelnummer Code Referencia	Cooling capacity Potenza frigorifera Kühlleistung Puissance frigorifique Potencia frigorífica EN14511 - A35A35	Power supply Alimentazione Stromversorgung Alimentation Alimentación	Dimensions Dimensioni Abmessungen Dimensions Medidas WxHxD	Conformity Conformità Konformität Conformité Conformidad
DEK04BT0B	410 W	230 V 1~ 50-60 Hz	259 x 260 x 481 mm	CE
DEK04BTUB	410 W	230 V 1~ 50-60 Hz	259 x 260 x 481 mm	CE - UL
DEK04CT0B	410 W	115 V 1~ 50-60 Hz	259 x 260 x 481 mm	CE
DEK08BT0B	820 W	230 V 1~ 50-60 Hz	341 x 339 x 600 mm	CE
DEK08BTUB	820 W	230 V 1~ 50-60 Hz	341 x 339 x 600 mm	CE - UL
DEK08CT0B	820 W	115 V 1~ 50-60 Hz	341 x 339 x 600 mm	CE
DEK08GT0B	820 W	400/440 V 2~ 50-60 Hz	341 x 339 x 600 mm	CE
DEK12BT0B	1150 W	230 V 1~ 50-60 Hz	401 x 415 x 572 mm	CE
DEK12BTUB	1150 W	230 V 1~ 50-60 Hz	401 x 415 x 572 mm	CE - UL
DEK12CT0B	1150 W	115 V 1~ 50-60 Hz	401 x 415 x 572 mm	CE
DEK12GT0B	1150 W	400/440 V 2~ 50-60 Hz	401 x 415 x 572 mm	CE
DEK15BT0B	1550 W	230 V 1~ 50-60 Hz	401 x 415 x 572 mm	CE
DEK15BTUB	1550 W	230 V 1~ 50-60 Hz	401 x 415 x 572 mm	CE - UL
DEK15CT0B	1550 W	115 V 1~ 50-60 Hz	401 x 415 x 572 mm	CE
DEK15GT0B	1550 W	400/440 V 2~ 50-60 Hz	401 x 415 x 572 mm	CE
DEK20BT0B	2050 W	230 V 1~ 50-60 Hz	401 x 415 x 572 mm	CE
DEK20CT0B	2050 W	115 V 1~ 50-60 Hz	401 x 415 x 572 mm	CE
DEK20LT0B	2050 W	400 V 3~ 50-60 Hz	401 x 415 x 572 mm	CE
DEK20NTUB	2050 W	460 V 3~ 60 Hz	401 x 415 x 572 mm	CE - UL
DEK30BT0B	2900 W	230 V 1~ 50-60 Hz	492 x 496 x 784 mm	CE
DEK30LT0B	2900 W	400 V 3~ 50-60 Hz	492 x 496 x 784 mm	CE
DEK30NTUB	2900 W	460 V 3~ 60 Hz	492 x 496 x 784 mm	CE - UL
DEK40BT0B	3850 W	230 V 1~ 50-60 Hz	492 x 496 x 784 mm	CE
DEK40LT0B	3850 W	400 V 3~ 50-60 Hz	492 x 496 x 784 mm	CE
DEK40NTUB	3850 W	460 V 3~ 60 Hz	492 x 496 x 784 mm	CE - UL

EMO

- Wall-mount air conditioners for outdoor applications
- Condizionatori da parete per applicazioni outdoor
- Klimageräte zur Installation an der Wand für Outdoor-Anwendungen
- Climatiseurs à montage mural pour applications extérieures
- Acondicionadores de pared para aplicaciones al aire libre



Item Codice Artikelnummer Code Referencia	Cooling capacity Potenza frigorifera Kühlleistung Puissance frigorifique Potencia frigorífica EN14511 - A35A35	Power supply Alimentazione Stromversorgung Alimentation Alimentación	Dimensions Dimensioni Abmessungen Dimensions Medidas WxHxD	Conformity Conformità Konformität Conformité Conformidad
EMO04BM1B	380 W	230 V 1~ 50-60 Hz	300 x 572 x 205 mm	CE
EMO04CM1B	380 W	115 V 1~ 50-60 Hz	300 x 572 x 205+35 mm	CE
EMO06BM1B	640 W	230 V 1~ 50-60 Hz	331 x 718 x 235 mm	CE
EMO06CM1B	640 W	115 V 1~ 50-60 Hz	331 x 718 x 235+42 mm	CE
EMO06GM1B	640 W	400/440 V 2~ 50-60 Hz	331 x 718 x 235+58 mm	CE
EMO08BM1B	820 W	230 V 1~ 50-60 Hz	363 x 895 x 239 mm	CE
EMO08CM1B	820 W	115 V 1~ 50-60 Hz	363 x 895 x 239+42 mm	CE
EMO08GM1B	820 W	400/440 V 2~ 50-60 Hz	363 x 895 x 239+58 mm	CE
EMO10BM1B	1000 W	230 V 1~ 50-60 Hz	363 x 895 x 239 mm	CE
EMO10CM1B	1000 W	115 V 1~ 50-60 Hz	363 x 895 x 239+42 mm	CE
EMO10GM1B	1000 W	400/440 V 2~ 50-60 Hz	363 x 895 x 239+58 mm	CE
EMO12BM1B	1250 W	230 V 1~ 50-60 Hz	415 x 1109 x 261 mm	CE
EMO12CM1B	1250 W	115 V 1~ 50-60 Hz	415 x 1109 x 261 mm	CE
EMO12GM1B	1250 W	400/440 V 2~ 50-60 Hz	415 x 1109 x 261 mm	CE
EMO16BM1B	1600 W	230 V 1~ 50-60 Hz	415 x 1109 x 261 mm	CE
EMO16CM1B	1600 W	115 V 1~ 50-60 Hz	415 x 1109 x 261 mm	CE
EMO16GM1B	1600 W	400/440 V 2~ 50-60 Hz	415 x 1109 x 261 mm	CE
EMO20BM1B	2000 W	230 V 1~ 50-60 Hz	415 x 1109 x 261 mm	CE
EMO20CM1B	2000 W	115 V 1~ 50-60 Hz	415 x 1109 x 261 mm	CE
EMO20LM1B	2000 W	400 V 3~ 50-60 Hz	415 x 1109 x 261 mm	CE
EMO30BM1B	2900 W	230 V 1~ 50-60 Hz	512 x 1417 x 365 mm	CE
EMO30LM1B	2900 W	400 V 3~ 50-60 Hz	512 x 1417 x 365 mm	CE
EMO40BM1B	3850 W	230 V 1~ 50-60 Hz	512 x 1417 x 365 mm	CE
EMO40LM1B	3850 W	400 V 3~ 50-60 Hz	512 x 1417 x 365 mm	CE
EMO60MMEB	5800 W	400 V 3~ 50 Hz	600 x 2000 x 387 mm	CE
EMO60NMEB	6050 W	460 V 3~ 60 Hz	600 x 2000 x 387 mm	CE
EMO80MMEB	7600 W	400 V 3~ 50 Hz	800 x 2000 x 387 mm	CE
EMO80NMEB	7950 W	460 V 3~ 60 Hz	800 x 2000 x 387 mm	CE
EMOA0MMEB	9400 W	400 V 3~ 50 Hz	800 x 2000 x 387 mm	CE
EMOA0NMEB	9850 W	460 V 3~ 60 Hz	800 x 2000 x 387 mm	CE

BLU-BIT

- Air-water heat exchangers
- Scambiatori di calore aria-acqua
- Luft/Wasser-Wärmetauscher
- Échangeurs de chaleur air - eau
- Intercambiadores de calor aire-agua



Item Codice Artikelnummer Code Referencia	Cooling capacity Potenza frigorifera Kühlleistung Puissance frigorifique Potencia frigorífica W10A35	Power supply Alimentazione Stromversorgung Alimentation Alimentación	Dimensions Dimensioni Abmessungen Dimensions Medidas WxHxD	Conformity Conformità Konformität Conformité Conformidad
BIT25BX0B	2500 W	230 V 1~ 50-60 Hz	400 x 270 x 540 mm	CE
BIT25CX0B	2500 W	115 V 1~ 50-60 Hz	400 x 270 x 540 mm	CE
BLU10BX0B	1000 W	230 V 1~ 50-60 Hz	311 x 453 x 115 mm	CE
BLU10BXUB	1000 W	230 V 1~ 50-60 Hz	311 x 453 x 115 mm	CE - UL
BLU10CX0B	1000 W	115 V 1~ 50-60 Hz	311 x 453 x 115 mm	CE
BLU18BX0B	1750 W	230 V 1~ 50-60 Hz	398 x 901 x 137 mm	CE
BLU18BXUB	1750 W	230 V 1~ 50-60 Hz	398 x 901 x 137 mm	CE - UL
BLU18CX0B	1750 W	115 V 1~ 50-60 Hz	398 x 901 x 137 mm	CE
BLU25BX0B	2500 W	230 V 1~ 50-60 Hz	398 x 901 x 137 mm	CE
BLU25BXUB	2500 W	230 V 1~ 50-60 Hz	398 x 901 x 137 mm	CE - UL
BLU25CX0B	2500 W	115 V 1~ 50-60 Hz	398 x 901 x 137 mm	CE
BLU35BX0B	3500 W	230 V 1~ 50-60 Hz	398 x 1148 x 163 mm	CE
BLU35BXUB	3500 W	230 V 1~ 50-60 Hz	398 x 1148 x 163 mm	CE - UL
BLU35CX0B	3500 W	115 V 1~ 50-60 Hz	398 x 1148 x 163 mm	CE
BLU45BX0B	4500 W	230 V 1~ 50-60 Hz	398 x 1148 x 163 mm	CE
BLU45BXUB	4500 W	230 V 1~ 50-60 Hz	398 x 1148 x 163 mm	CE - UL
BLU45CX0B	4500 W	115 V 1~ 50-60 Hz	398 x 1148 x 163 mm	CE
BLU60BX0B	6000 W	230 V 1~ 50-60 Hz	450 x 1502 x 163 mm	CE
BLU60BXUB	6000 W	230 V 1~ 50-60 Hz	450 x 1502 x 163 mm	CE - UL
BLU60CX0B	6000 W	115 V 1~ 50-60 Hz	450 x 1502 x 163 mm	CE
BLU60GX0B	6000 W	400/440 V 2~ 50-60 Hz	450 x 1502 x 163 mm	CE
BLUA0BX0B	10000 W	230 V 1~ 50-60 Hz	797 x 1935 x 206 mm	CE
BLUA0GX0B	10000 W	400/440 V 2~ 50-60 Hz	797 x 1935 x 206 mm	CE
BLUA5BX0B	15000 W	230 V 1~ 50-60 Hz	797 x 1935 x 206 mm	CE
BLUA5GX0B	15000 W	400/440 V 2~ 50-60 Hz	797 x 1935 x 206 mm	CE

MIX

- Air-air heat exchangers
- Scambiatori di calore aria-aria
- Luft/Luft-Wärmetauscher
- Échangeurs de chaleur air - air
- Intercambiadores de calor aire-aire

Item Codice Artikelnummer Code Referencia	Specific cooling power Potenza termica specifica Spezifische thermische Leistung Puissance thermique spécifique Potencia térmica específica	Power supply Alimentazione Stromversorgung Alimentation Alimentación	Dimensions Dimensioni Abmessungen Dimensions Medidas WxHxD	Conformity Conformità Konformität Conformité Conformidad
MIX22BX0B	22 W/K	230 V 1~ 50-60 Hz	189 x 413 x 149 mm	CE
MIX22CX0B	22 W/K	115 V 1~ 50-60 Hz	189 x 413 x 149 mm	CE
MIX36BX0B	36 W/K	230 V 1~ 50-60 Hz	316 x 771 x 103 mm	CE
MIX36CX0B	36 W/K	115 V 1~ 50-60 Hz	316 x 771 x 103 mm	CE
MIX50BX0B	50 W/K	230 V 1~ 50-60 Hz	316 x 771 x 103 mm	CE
MIX50CX0B	50 W/K	115 V 1~ 50-60 Hz	316 x 771 x 103 mm	CE
MIX80BX0B	80 W/K	230 V 1~ 50-60 Hz	317 x 1260 x 148 mm	CE
MIX80CX0B	80 W/K	115 V 1~ 50-60 Hz	317 x 1260 x 148 mm	CE

