

TCW Minichiller

- Industrial water chillers
- Refrigeratori industriali per acqua
- Wasserkühlgeräte für Industrieanwendungen
- Réfrigérateurs industriels pour eau
- Refrigeradores industriales para agua



Item Codice Artikelnummer Code Referencia	Cooling capacity Capacità di raffreddamento Kühlleistung Capacité de refroidissement Capacidad de enfriamiento	Power supply Alimentazione Stromversorgung Alimentation Alimentación	Dimensions Dimensioni Abmessungen Dimensions Medidas WxHxD
TCW08	900/1100 W	230 V 1~ 50-60 Hz	725 x 367 x 454 mm
TCW12	1600/1900 W	230 V 1~ 50-60 Hz	725 x 367 x 454 mm
TCW19	2200/2550 W	230 V 1~ 50-60 Hz	725 x 367 x 454 mm
TCW30	3000/3450 W	230 V 1~ 50-60 Hz	725 x 367 x 454 mm
TCW40	3900/4450 W	230 V 1~ 50-60 Hz	725 x 367 x 454 mm

TCO Minichiller

- Industrial oil chillers
- Refrigeratori industriali per olio
- Ölkühlgeräte für Industrieanwendungen
- Réfrigérateurs industriels pour huile
- Refrigeradores industriales para aceite



Item Codice Artikelnummer Code Referencia	Cooling capacity Capacità di raffreddamento Kühlleistung Capacité de refroidissement Capacidad de enfriamiento	Power supply Alimentazione Stromversorgung Alimentation Alimentación	Dimensions Dimensioni Abmessungen Dimensions Medidas WxHxD
TCO08	900/1100 W	230 V 1~ 50-60 Hz	725 x 367 x 454 mm
TCO12	1600/1900 W	230 V 1~ 50-60 Hz	725 x 367 x 454 mm
TCO19	2200/2550 W	230 V 1~ 50-60 Hz	725 x 367 x 454 mm
TCO30	3000/3450 W	230 V 1~ 50-60 Hz	725 x 367 x 454 mm
TCO40	3900/4450 W	230 V 1~ 50-60 Hz	725 x 367 x 454 mm

TCW

- Industrial water chillers
- Refrigeratori industriali per acqua
- Wasserkühlgeräte für Industrieanwendungen
- Réfrigérateurs industriels pour eau
- Refrigeradores industriales para agua

Item Codice Artikelnummer Code Referencia	Cooling capacity Capacità di raffreddamento Kühlleistung Capacité de refroidissement Capacidad de enfriamiento	Power supply Alimentazione Stromversorgung Alimentation Alimentación	Dimensions Dimensioni Abmessungen Dimensions Medidas WxHxD
TCW15	1600/1900 W	230 V 1~ 50-60 Hz	595 x 995 x 678 mm
TCW22	2200/2550 W	230 V 1~ 50-60 Hz	595 x 995 x 678 mm
TCW22	2200 W	400 V 3~ 50 Hz	595 x 995 x 678 mm
TCW36	3300/3900 W	230 V 1~ 50-60 Hz	595 x 995 x 678 mm
TCW36	3300 W	400 V 3~ 50 Hz	595 x 995 x 678 mm
TCW44	4400 W	400 V 3~ 50 Hz	595 x 995 x 678 mm
TCW55	5300 W	400 V 3~ 50 Hz	595 x 995 x 678 mm
TCW56	6000 W	400 V 3~ 50 Hz	681 x 1236 x 805 mm
TCW70	8100 W	400 V 3~ 50 Hz	681 x 1236 x 805 mm
TCW91	9200 W	400 V 3~ 50 Hz	681 x 1236 x 805 mm
TCWA0	10900 W	400 V 3~ 50 Hz	681 x 1236 x 805 mm
TCWA2	12300 W	400 V 3~ 50 Hz	744 x 1335 x 1360 mm
TCWA4	16400 W	400 V 3~ 50 Hz	744 x 1335 x 1360 mm
TCWA7	17800 W	400 V 3~ 50 Hz	744 x 1335 x 1360 mm
TCWA9	20700 W	400 V 3~ 50 Hz	744 x 1335 x 1360 mm
TCWB2	23000 W	400 V 3~ 50 Hz	844 x 1485 x 1759 mm
TCWB7	28300 W	400 V 3~ 50 Hz	844 x 1485 x 1759 mm
TCWC1	32800 W	400 V 3~ 50 Hz	844 x 1485 x 1759 mm
TCWC8	37600 W	400 V 3~ 50 Hz	844 x 1485 x 1759 mm
TCWD4	41400 W	400 V 3~ 50 Hz	1094 x 1599 x 2062 mm
TCWE0	46100 W	400 V 3~ 50 Hz	1094 x 1599 x 2062 mm
TCWE4	56600 W	400 V 3~ 50 Hz	1094 x 1599 x 2062 mm
TCWF7	65600 W	400 V 3~ 50 Hz	1094 x 1599 x 2062 mm
TCWG8	75200 W	400 V 3~ 50 Hz	1094 x 1599 x 2062 mm
TCWH2	82800 W	400 V 3~ 50 Hz	1508 x 1870 x 2554 mm
TCWI3	92200 W	400 V 3~ 50 Hz	1508 x 1870 x 2554 mm
TCWM4	113200 W	400 V 3~ 50 Hz	1508 x 1870 x 2554 mm
TCWO1	131200 W	400 V 3~ 50 Hz	1508 x 1870 x 2554 mm
TCWQ0	150400 W	400 V 3~ 50 Hz	1508 x 1870 x 2554 mm
TCWR2	166600 W	400 V 3~ 50 Hz	1904 x 2235 x 4304 mm
TCWS4	184400 W	400 V 3~ 50 Hz	1904 x 2235 x 4304 mm
TCWT6	226400 W	400 V 3~ 50 Hz	1904 x 2235 x 4304 mm
TCWV3	262400 W	400 V 3~ 50 Hz	1904 x 2235 x 4304 mm
TCWZ0	300800 W	400 V 3~ 50 Hz	1904 x 2235 x 4304 mm
TCW3E	355000 W	400 V 3~ 50 Hz	2194 x 2390 x 5804 mm
TCW4A	400000 W	400 V 3~ 50 Hz	2194 x 2390 x 5804 mm



LCW

- Negative temperature liquid chillers
- Refrigeratori di fluidi a temperature negative
- Mediumkühlgeräte für negative Temperaturen
- Réfrigérateurs de fluides à températures négatives
- Refrigeradores de fluidos a temperaturas negativas

Item Codice Artikelnummer Code Referencia	Cooling capacity Capacità di raffreddamento Kühlleistung Capacité de refroidissement Capacidad de enfriamiento	Power supply Alimentazione Stromversorgung Alimentation Alimentación	Dimensions Dimensioni Abmessungen Dimensions Medidas WxHxD
LCW15	2200 W	400 V 3~ 50 Hz	681 x 1236 x 805 mm
LCW22	3400 W	400 V 3~ 50 Hz	681 x 1236 x 805 mm
LCW45	6500 W	400 V 3~ 50 Hz	744 x 1334 x 1358 mm
LCW70	10450 W	400 V 3~ 50 Hz	744 x 1334 x 1358 mm
LCWA2	13000 W	400 V 3~ 50 Hz	844 x 1485 x 1759 mm
LCWA8	19600 W	400 V 3~ 50 Hz	844 x 1485 x 1759 mm
LCWB5	24100 W	400 V 3~ 50 Hz	1094 x 1599 x 2062 mm
LCWC4	34800 W	400 V 3~ 50 Hz	1094 x 1599 x 2062 mm



TCO

- Industrial oil chillers
- Refrigeratori industriali per olio
- Ölkühlgeräte für Industrieanwendungen
- Réfrigérateurs industriels pour huile
- Refrigeradores industriales para aceite

Item Codice Artikelnummer Code Referencia	Cooling capacity Capacità di raffreddamento Kühlleistung Capacité de refroidissement Capacidad de enfriamiento	Power supply Alimentazione Stromversorgung Alimentation Alimentación	Dimensions Dimensioni Abmessungen Dimensions Medidas WxHxD
TCO15	1600/1900 W	230 V 1~ 50-60 Hz	595 x 995 x 678 mm
TCO22	2200/2550 W	230 V 1~ 50-60 Hz	595 x 995 x 678 mm
TCO22	2200 W	400 V 3~ 50 Hz	595 x 995 x 678 mm
TCO36	3300/3900 W	230 V 1~ 50-60 Hz	595 x 995 x 678 mm
TCO36	3300 W	400 V 3~ 50 Hz	595 x 995 x 678 mm
TCO44	4400 W	400 V 3~ 50 Hz	595 x 995 x 678 mm
TCO55	5300 W	400 V 3~ 50 Hz	595 x 995 x 678 mm
TCO56	6000 W	400 V 3~ 50 Hz	681 x 1236 x 805 mm
TCO70	8100 W	400 V 3~ 50 Hz	681 x 1236 x 805 mm
TCO91	9200 W	400 V 3~ 50 Hz	681 x 1236 x 805 mm
TCOA0	10900 W	400 V 3~ 50 Hz	681 x 1236 x 805 mm
TCOA2	12300 W	400 V 3~ 50 Hz	744 x 1335 x 1360 mm
TCOA4	16400 W	400 V 3~ 50 Hz	744 x 1335 x 1360 mm
TCOA7	17800 W	400 V 3~ 50 Hz	744 x 1335 x 1360 mm
TCOA9	20700 W	400 V 3~ 50 Hz	744 x 1335 x 1360 mm
TCOB2	23000 W	400 V 3~ 50 Hz	844 x 1485 x 1759 mm
TCOB7	28300 W	400 V 3~ 50 Hz	844 x 1485 x 1759 mm
TCOC1	32800 W	400 V 3~ 50 Hz	844 x 1485 x 1759 mm
TCOC8	37600 W	400 V 3~ 50 Hz	844 x 1485 x 1759 mm
TCOD4	41400 W	400 V 3~ 50 Hz	1094 x 1599 x 2062 mm
TCOE0	46100 W	400 V 3~ 50 Hz	1094 x 1599 x 2062 mm
TCOE4	56600 W	400 V 3~ 50 Hz	1094 x 1599 x 2062 mm
TCOF7	65600 W	400 V 3~ 50 Hz	1094 x 1599 x 2062 mm
TCOG8	75200 W	400 V 3~ 50 Hz	1094 x 1599 x 2062 mm



TCU

- Industrial chillers for dirty oil
- Refrigeratori industriali per oli inquinati
- Kühlgeräte für verunreinigte Öle für Industrieanwendungen
- Réfrigérateurs industriels pour huiles polluées
- Refrigeradores industriales para aceites contaminados

Item Codice Artikelnummer Code Referencia	Cooling capacity Capacità di raffreddamento Kühlleistung Capacité de refroidissement Capacidad de enfriamiento	Power supply Alimentazione Stromversorgung Alimentation Alimentación	Dimensions Dimensioni Abmessungen Dimensions Medidas WxHxD
TCU15	1600/1900 W	230 V 1~ 50-60 Hz	595 x 995 x 678 mm
TCU22	2200/2550 W	230 V 1~ 50-60 Hz	595 x 995 x 678 mm
TCU22	2200 W	400 V 3~ 50 Hz	595 x 995 x 678 mm
TCU36	3300/3900 W	230 V 1~ 50-60 Hz	595 x 995 x 678 mm
TCU36	3300 W	400 V 3~ 50 Hz	595 x 995 x 678 mm
TCU44	4400 W	400 V 3~ 50 Hz	595 x 995 x 678 mm
TCU55	5300 W	400 V 3~ 50 Hz	595 x 995 x 678 mm
TCU56	6000 W	400 V 3~ 50 Hz	681 x 1236 x 805 mm
TCU70	8100 W	400 V 3~ 50 Hz	681 x 1236 x 805 mm
TCU91	9200 W	400 V 3~ 50 Hz	681 x 1236 x 805 mm
TCUA0	10900 W	400 V 3~ 50 Hz	681 x 1236 x 805 mm



TCI

- Immersion coil chillers
- Refrigeratori a serpentina immersa
- Kühlgeräte mit Tauchschlangenrohr
- Réfrigérateurs à serpentin immergé
- Refrigeradores de serpentín sumergido

Item Codice Artikelnummer Code Referencia	Cooling capacity Capacità di raffreddamento Kühlleistung Capacité de refroidissement Capacidad de enfriamiento	Power supply Alimentazione Stromversorgung Alimentation Alimentación	Dimensions Dimensioni Abmessungen Dimensions Medidas WxHxD
TCI56	6000/7100 W	400 V 3~ 50 Hz/460 V 3~ 60 Hz	550 x 1432 x 550 mm
TCI70	8100/9650 W	400 V 3~ 50 Hz/460 V 3~ 60 Hz	550 x 1432 x 550 mm
TCI91	9200/11000 W	400 V 3~ 50 Hz/460 V 3~ 60 Hz	550 x 1432 x 550 mm
TCIA2	12300/14600 W	400 V 3~ 50 Hz/460 V 3~ 60 Hz	549 x 1636 x 1002 mm
TCIA4	16400/16200 W	400 V 3~ 50 Hz/460 V 3~ 60 Hz	549 x 1636 x 1002 mm
TCIA7	17800/20450 W	400 V 3~ 50 Hz/460 V 3~ 60 Hz	549 x 1636 x 1002 mm



SAW

- Water-air heat exchangers
- Scambiatori acqua-aria
- Wasser/Luft-Wärmetauscher
- Échangeurs eau - air
- Intercambiadores agua-aire

Item Codice Artikelnummer Code Referencia	Cooling capacity Capacità di raffreddamento Kühlleistung Capacité de refroidissement Capacidad de enfriamiento	Power supply Alimentazione Stromversorgung Alimentation Alimentación	Dimensions Dimensioni Abmessungen Dimensions Medidas WxHxD
SAW10	1500/1750 W	230 V 1~ 50-60 Hz	325 x 252 x 550 mm
SAW50	5000/5650 W	230 V 1~ 50-60 Hz	520 x 660 x 230 mm
SAWA0	10000 W	230 V 1~ 50 Hz	595 x 995 x 678 mm



TTW

- Temperature controllers
- Termoregolatori
- Temperaturregler
- Thermorégulateurs
- Termorreguladores

Item Codice Artikelnummer Code Referencia	Heating capacity Capacità di riscaldamento Heizleistung Capacité de chauffage Capacidad de calentamiento	Power supply Alimentazione Stromversorgung Alimentation Alimentación	Dimensions Dimensioni Abmessungen Dimensions Medidas WxHxD
TTW90	3000/6000 W	400 V 3~ 50 Hz	304 x 550 x 795 mm
TTW95	3000/6000/9000/12000 W	400 V 3~ 50 Hz	304 x 730 x 795 mm

