

SPINVISTA

SPINVISTA NEO

SPINVISTA EVO

High-tech Swiss Motor

Brushless DC motor with reverse polarity and overheat protection



360° Position

Installation position freely selectable

Large viewing area

Optimized housing design for a larger viewing area

ATEX protection optional

Motor and electronics fully potted, protected against sparking and humidity

Hard anodized aluminum housing surface

Resistant to abrasion and excellent thermal conductivity

Connection orientation configurable

Three positions selectable, sealing air connection on option

Responsive

Spin disk breaks in a few seconds to a non-critical speed and can be safely touched

Extremely watertight

Excellent protection against coolant thanks to labyrinth construction and optional overpressure

Proven installation

Mounting frame for adhesive mounting

Low height

<32 mm including mounting frame, also suitable for many cabin doors

DLC coating optional

Spin disk with special coating for particularly demanding applications



SPINVISTA EVO

Outer diameter
253 mm

Viewing area
ca. 284 cm²



SPINVISTA NEO

Outer diameter
290 mm

Viewing area
ca. 430 cm²



HEMA Maschinen- und Apparateschutz GmbH
Am Klinggraben 2, 63500 Seligenstadt, Germany
Phone: +49(0)6182/773-0 - Fax: +49(0)6182/773-35
info@hema-group.com - www.hema-group.com